

## **NH2 - AV System Startup – Dec. 2015**

Before entering auditorium, turn on lights, make sure breaker for stage lighting is off.

- 1 – Check heat, set to 18, HEAT, FAN ON
- 2 – Remove covers from equipment, check that all channels are off, faders down
- 3 – Patch Speaker and monitor sends
- 4 – Plug in sound board to wall by lighting panel
- 5 – Unlock and turn on master switch
- 6 – Check that all lighting is off, plug in lights 3 and 5 and toaster plugs (separate circuits)
- 7 – Plugin BIG lighting power
- 8 – Turn on breaker for Stage Lighting and Projector
- 9 – If needed turn on projector, hold ON button down for 5 seconds
- 10 – Plug in right front lighting to wall behind right front subwoofer
- 11 - Check heat, set to 18, HEAT, FAN ON
- 10 – Turn on upper LED right
- 11 – Turn on upper LED left
- 12 – Raise or lower center screen as needed
- 13 – Remove front cover and turn on main and sub amps, set volume to mark
- 14 – Connect monitor speakers as required
- 15 – Turn on monitor amps, set volume to mark

### **Shut down**

- 1 – Turn off monitor amps, turn volume off
- 2 – Disconnect monitor speakers
- 4 - Return monitor cables, turn off main amps and replace amp cover
- 5 – Turn off upper LED left
- 6 – Turn off upper LED right
- 7 – Unplug right front lighting
- 8 – Shut down upper projector by holding the ON button for 5 seconds and unplug
- 9 – Turn off all stage and LED lights
- 10 – Turn off all audio channels and return faders to off
- 11 – Check that stage lights are off!!, then unplug BIG lighting plug
- 12 – Unplug sound board from wall
- 13 – Turn off master switch and lock
- 14 - Re patch speaker and monitor sends
- 15 – Replace covers and lock
- 16 – Turn off lights and switch off breaker for stage lighting and projector